


URKISEAL 4020

Primer for Car Windows



DESCRIPTION

Black primer that turns into a hard, opaque film when it dries. It enables the adhesion of polyurethane sealants and can be used on different substrates: glass, aluminium, concrete, wood and plastic.

It can also be used as a barrier between the sealant and the paint to prevent migration of plasticisers.

COLORS

URKISEAL 4020	9005
---------------	------

SURFACE PREPARATION

Surfaces to be primed must be clean, dry and free of dust and grease. Cleaning can be done with URKISOL 88 depending on the sensitivity of the substrate to be painted (check the compatibility of the solvent used with the substrates).

USE




(Between 5°C and 40°C)

Shake before use for good homogenisation.

Apply with a brush or swab, in a fluid movement.

Reacts and hardens with ambient humidity after solvent evaporation. Once used, close the container again.

CAUTION: Do not open the container until it is to be used and do not use it after 24 hours from the time it is opened.

 Drying Time 20°C	10 - 15'
---	----------

DRY FILM CHARACTERISTICS



Recoatibility	After drying, apply URKISEAL 4000 within 1 hour.
---------------	--

SAFETY INSTRUCTIONS 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 5 and 25°C optimal.

Duration in the container: 12 months from manufacture in original unopened container. After this time, consult with BESA's Technical Department.

VOC 

The VOC content of URKISEAL 4020 is a maximum of 780 g/l in compliance with European regulation 2004/42/EC IIB(C) (780) <780 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**
