


URKIGLOSS Polish



DESCRIPTION

Effective and high quality polishing compound designed for all types of paints. Its formulation quickly removes polishing and sanding marks with P2500-P3000 grit. High level gloss and mirror-finished surfaces are achieved, without marks.

Its balanced composition in solid and liquid ingredients minimises the generation of dust, reducing contamination of the workplace.

High level of shining with medium abrasion power. It is versatile, suitable for both recently repaired and aged coatings.

Contains no silicones.

COLORS

URKIGLOSS	WHITE
-----------	-------

USE

It is important to apply appropriate and sufficient pressure on the polisher in the first coats on the surface to remove any marks or surface defects.

Polish with special soft sponge for brightening processes. Do not use polishing sponges.

Easy removal of residues with microfibre cloth.

	Cleaning	Clean and moisten
	Sanding	P2500 - P3000
	Polishing	1200 - 2000 RPM
	Cleaning	Clean with a microfibre cloth

SAFETY INSTRUCTIONS 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

VOC 

The VOC content of URKIGLOSS is a maximum of 200 g/l in compliance with European regulation 2004/42/EC IIB(A) (200) <200g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**
